



INSUTEX

Complies with DIN 4117

DESCRIPTION :

INSUTEX is a cold applied adhesive bituminous compound formulated from ductile high quality asphalt, selected solvent and special additives.

Color: Black.

FIELDS OF APPLICATION:

INSUTEX is good adhesive for :-

- Vinyl Tiles and Vinyl Sheet
- Polystyrene foam.
- Roofing Felt.

RATE OF APPLICATION :

- Vinyl sheet and tile 0.25 Liter/m².
- Roofing felt 0.50 – 0.75 Liter/m².
- Thermal insulation 0.50 – 0.75 Liter/m².

TECHNICAL DATA

PROPERTIES	UNITS	RESULTS	TEST METHOD
Density at 25 °C	Kg/L	1.0	ASTM D-70
Viscosity at 50 °C	CPS	3000	BROOKFIELD
Softening Point base from distillation	°C	80 - 90	ASTM D-36
Penetration base from distillation	dm m	18 - 22	ASTM D-5
Setting time to apply	minute	30	
Drying time to walk	Hrs	12 - 24	
Service temperature	°C	15 - 50	ASTM G-53
Resistance to : Heat, Water, Salt, Sunlight		Good	ASTM G-53

TEMPERATURE LIMIT : Complies with DIN 4117.

PACKAGING : 5 Liters and 20 Liters pails.

CAUTION : INSUTEX contains flammable organic solvents.

Don't smoke or use open flame during application or during the first hour of drying.

SHELF LIFE : 12 months if stored in good conditions and in undamaged containers.

NB: The above products data is subject to technical updating without prior notice due to technological research and development pursued by INSUMAT.

Head Office: 20 Haroun St. Dokki Giza, Egypt.

P.O. Box 101 – Orman – Giza

Tel. : +202 374 98 377 Fax.: +202 374 82 862

Factory: Tamouh – Giza – km14, Upper Egypt Road

Tel. : +202 381 72 218 +202 381 72 818 Fax.: +202 381 72 918

E-mail: info@insumat.com

website: www.insumat.com

